

Free-Machining CW724R

CuZn21Si3P








Chemistry composition

EN12164

Cu	Pb	Fe	Al	Ni	Sn	Mn	P	Si	Zn	Others
75.0-77.0%	0.1% max	0.3% max	0.05% max	0.2% max	0.3% max	0.05% max	0.02-0.1%	2.7-3.5%	Rem.	0.2% max

Shapes & sizes

 Round 5-110 mm	 Hex/Oct. 6-60 mm	 Square Consult Mill	 Flat Consult Mill	 Profile Consult Mill
---	--	---	--	--

Standard Length 3-4 M

Mechanical properties

Temper	Diameter (Round)	Diameter (Hex)	Tensile Strength, min (Mpa)	Rpo.2 min/max (Mpa)	Elongation min (%)	Hardness min/max (HBW)
M	All as manufactured					
R500	6-80	35-80	500	0//450	15	N
H130	6-80	35-80	N	N	N	70/100
R600	10-40	15-40	600	300/-	12	N
H150	10-40	15-40	N	N	N	150/220
R670	2-20	2-15	670	400/-	10	N
H170	2-20	2-15	N	N	N	170/-

Diameter tolerances - EN12164 Table 14

From	up to and including	Class A (Round)	Class B (Round)	Class C (Round)	Tolerances on width across-flats of regular polygonal rod
3	6	+0 / -0.05	+0 / -0.03	+0 / -0.02	+0 / -0.08
6	10	+0 / -0.06	+0 / -0.036	+0 / -0.025	+0 / -0.09
10	18	+0 / -0.07	+0 / -0.043	-	+0 / -0.11
18	30	+0 / -0.08	+0 / -0.052	-	+0 / -0.13
30	50	+0 / -0.16	-	-	+0 / -0.16
50	80	+0 / -0.19	-	-	+0 / -0.19
80	110	+2.0	-	-	-

* Stock to Class A

Bar Ends

Shape	Sizes (mm)	Bar/Rod Chamfering
RND	Up to & including 60	one side pointed other chamfered * Above these sizes - Saw Cut
HEX	Up to & including 50	
SQR	Up to & including 40	

Packaging: 1000 kg bundle.

*all size range of 11 mm and below (all shapes) will be packed in fumigated wooden boxes.

Traceability: Barcoded labels on strap